

BB-2J6024BA-150

CELLULAR / LTE MIMO Screw Mount

Key Features

Cable 1 - 2: CELLULAR / LTE

- 698-960 MHz
- 1710-2170 MHz
- 2500-2700 MHz

Screw Mount

Ground Plane Independent

Dimensions 80 x 74 x 14.7 mm

Certificates: IP67



1. Antenna and electrical specifications

Cable 1

Parameters	CELLULAR / LTE Antenna		
	2G,3G and 4G		
Standards	2G,3G and 4G		
Band (MHz)	700/850/900	1700/1800/1900/2100	2600
Frequency (MHz)	698-960	1710-2170	2500-2700
Return Loss (dB)	~-9.4	~-7.8	~-19.4
VSWR	~2.1:1	~2.4:1	~1.3:1
Efficiency (%)	~31.5	~30.4	~43.8
Peak Gain (dBi)	~-0.7	~-2.7	~-4.3
Average Gain (dB)	~-5.0	~-5.2	~-3.6
Impedance (Ohm)	50		
Polarisation	Linear		
Radiation Pattern	Omni-Directional		
Max. Input Power (W)	25		
Connector Type	SMA-Male Standard		
Cable Length	150cm Standard		
Cable Type	DACAR302 Standard		

Cable 2

Parameters	CELLULAR / LTE Antenna		
	2G,3G and 4G		
Standards	2G,3G and 4G		
Band (MHz)	700/850/900	1700/1800/1900/2100	2600
Frequency (MHz)	698-960	1710-2170	2500-2700
Return Loss (dB)	~-9.9	~-8.1	~-19.5
VSWR	~2.0:1	~2.3:1	~1.3:1
Efficiency (%)	~33.0	~29.5	~43.1
Peak Gain (dBi)	~-1.4	~-2.2	~-4.4
Average Gain (dB)	~-4.8	~-5.5	~-3.7
Impedance (Ohm)	50		
Polarisation	Linear		
Radiation Pattern	Omni-Directional		
Max. Input Power (W)	25		
Connector Type	SMA-Male Standard		
Cable Length	150cm Standard		
Cable Type	DACAR302 Standard		

Antenna Measurement Conditions:

Mounted on 30 x 30 x 0.25 cm ABS Plate

200 cm of Cable DACAR302



Measured in Certified CTIA 3D Anechoic Chamber




2. Mechanical and environmental specifications

Specifications	BB-2J7050BGFA-150
Mounting Type	Screw Mount
Dimensions (mm)	80 x 74 x 14.7
Radome	ABS
Radome color	Black
Operating Temperature (C)	-40 to +85
Storage Temperature (C)	-40 to +85
Substance Compliance	RoHS
Certificates	IP67



3. Antenna parameters




Cable 1: CELLULAR/LTE






Cable 2: CELLULAR/LTE






ISOLATION FOR CABLES 1 AND 2



ENVELOPE CORRELATION COEFFICIENT FOR CABLES 1 AND 2









Table 1: CELLULAR/LTE




750 and 850 MHz Radiation pattern



940 and 1750 MHz Radiation pattern




1850 and 1950 MHz Radiation pattern




2100 and 2600 MHz Radiation pattern


Table 2: CELLULAR/LTE




750 and 850 MHz Radiation pattern



940 and 1750 MHz Radiation pattern




1850 and 1950 MHz Radiation pattern



2100 and 2600 MHz Radiation pattern

4. Antenna drawings



* Dimensions after mounting

5. Antenna Images

